



Kisi Controller Pro – KCP50



4 Dry or Wet Contacts • Door Contact Inputs • ReX Inputs • Cloud Connected

Power Input	16V DC (included) 12V DC external power supply when used with dry contacts 24V DC external power supply when used with wet contacts
Powering Locks	Supply low voltage power for electric strike. Total amount pulled from relays not to exceed 2A
Internet Connectivity	Ethernet (CAT6) and/or WiFi
Signal Wiring	4 Dry or Wet relays wiring to door security hardware 4 Door Contact Sensors 4 Request to Exit Sensors see wiring diagram
Dimensions	Height 12", Width 9", Depth 3", Access Board: 161 x 81MM
Mounting	Screw-in-Wall
Included Accessoires	Power Supply

[Read More](#)



Kisi Credentials

iOS / Android • Cards • Tags • Compatibility



Kisi Mobile Credential	iOS / Android
Kisi Black Pass	Black Kisi Pass (default), MiFare DesFire EV1 platform, 128bit AES encryption
Kisi White Pass	Kisi Pass with blank white front for card printing of IDs
Kisi Custom Pass	Kisi Pass available with your custom design. 200 minimum order, 6 weeks turnaround.
Kisi Tag	Enables existing building prox card
Kisi Fob	Fits on your keychain

[Read More](#)